



FLOTATION PRO

710/50R26.5 170 D

MEETS THE HIGH DEMANDS OF PROFESSIONALS

The radial construction and flat contour make this an excellent choice for machines on grassland

Features Benefits



MINIMAL RUTTING,
LONG LIFESPAN

High rubber content in profile



GOOD FLOTATION
PROPERTIES, HIGH
COMFORT LEVEL

Flexible and strong carcass



NO DAMAGE TO
VULNERABLE CROP

Flat contour & rounded
shoulders

VREDESTEIN

FLOTATION PRO

Specifications

710/50R26.5 170 D

Code 8714692198700

Service Description	170 D
Tyre Construction	Radial
Tubetype / Tubeless	Tubeless



Static Dimensions +/- 2%

Section width	710	mm
Overall Diameter	1360	mm
Static Loaded Radius	620	mm

Dynamic Dimensions +/- 2%

Rolling Circumference	4200	mm
Dynamic Loaded Radius		mm

Rims

Recommended Rim	AG 24.00
Permitted Rim	0

Other Details

75% tyre volume	374	liter		
SRI / RCI Label	650	SRI		
Nominal Tyre pressure	0	kPa	0	psi
Original Tread Depth	19	mm	24	32nd

		Tyre pressure (bar)							
		1,20	1,60	2,00	2,40	2,80	3,20	3,60	4,00
		Load capacity per tyre (kg)							
Speed (km/h)	10	4450	5440	6310	7235	8145	9000	9900	10800
	25	3905	4775	5540	6350	7150	7900	8690	9480
	30	3735	4565	5290	6070	6835	7550	8305	9060
	40	3365	4110	4765	5465	6155	6800	7480	8160
	50	2990	3655	4240	4860	5475	6050	6655	7260
	65	2475	3020	3505	4020	4525	5000	5500	6000
	70	2250	2750	3190	3655	4120	4550	5005	5460

VREDESTEIN

It is recommended not to exceed the maximum tyre pressures shown in the tables

For radial tractor drive tyres applies: For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar

10C: Cyclic field activities at low torque up to 10 km/h where the maximum load per tyre fluctuates greatly and where the maximum load is carried not more than 1500 meter. For slopes of over 10% up to 20% increase the inflation pressure with 0,5 bar. For slopes over 20% only the basic load capacity applies.

10Cl: Cyclic activities at low torque up to 10 km/h where the maximum load per tyre fluctuates greatly and where the maximum load is carried not more than 600 meter.

10H: Field activities where high torque is required at maximum 10 km/h.

10L: Activities where low torque is required at maximum 10 km/h.

15C: Cyclic field activities at low torque up to 15 km/h where the maximum load per tyre fluctuates greatly and where the maximum load is carried not more than 1500 meter. For slopes of over 10% up to 20% increase the inflation pressure with 0,5 bar. For slopes over 20% only the basic load capacity applies.

**In case these tyres are driven, 70% of the load capacity in non-driven application applies.

***When fitted on free-rolling steering wheels of self propelled agricultural equipment, tyre load capacities are 80% of the loads for free-rolling applications.

VEDESTEIN