

FLOTXTRA



SOIL PROTECTION

- Rounded tread lug edges ensure optimal protection of crop areas
- Wide tread lugs result in lower soil compaction
- Stiff tread design ensures even pressure distribution and a stable footprint.

LATERAL STABILITY

- Special tread block design ensures excellent lateral grip
- Multi-oriented tread block faces ensure excellent self-cleaning properties.

DURABILITY & MILEAGE

- Full-steel construction for excellent durability and damage resistance
- Advanced rubber compound construction ensures excellent mileage performance.

SAFETY

- Limited stone and mud retention due to an advanced tread geometry design
- Excellent directional stability caused by the nearly continuous central rib.

SIZE	LOAD & SPEED	TYPE	RIM	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	STATIC LOADED RADIUS (mm)	ROLLING CIRC. (mm)	TREAD DEPTH (mm)
560/60R22.5 IMP	161D	TL	AG16.00 x 22.5	543	1244	560	3770	19

TYRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)

Service Speed (mph/kph)	12 psi	17 psi	23 psi	29 psi	35 psi	41 psi	46 psi	52 psi	58 psi	73 psi
	0.8 bar	1.2 bar	1.6 bar	2 bar	2.4 bar	2.8 bar	3.2 bar	3.6 bar	4 bar	5 bar
5/10	6050/2745	7530/3415	9180/4165	10650/4830	12300/5580	13770/6245	15235/6910	16885/7660	18355/8325	
40/65	3360/1525	4180/1895	5105/2315	5920/2685	6835/3100	7650/3470	8465/3840	9380/4255	10195/4625	