

FLOTXTRA



SOIL PROTECTION

- Rounded tread lug edges ensure optimal protection of crop areas
- Wide tread lugs result in lower soil compaction
- Stiff tread design ensures even pressure distribution and a stable footprint.

LATERAL STABILITY

- Special tread block design ensures excellent lateral grip
- Multi-oriented tread block faces ensure excellent self-cleaning properties.

DURABILITY & MILEAGE

- Full-steel construction for excellent durability and damage resistance
- Advanced rubber compound construction ensures excellent mileage performance.

SAFETY

- Limited stone and mud retention due to an advanced tread geometry design
- Excellent directional stability caused by the nearly continuous central rib.

SIZE	LOAD & SPEED	TYPE	RIM	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	STATIC LOADED RADIUS (mm)	ROLLING CIRC. (mm)	TREAD DEPTH (mm)
600/55R26.5	165D	TL	AG20.00 x 26.5	611	1333	600	4040	20

TYRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)

Service Speed (mph/kph)	12 psi	17 psi	23 psi	29 psi	35 psi	41 psi	46 psi	52 psi	58 psi	73 psi
	0.8 bar	1.2 bar	1.6 bar	2 bar	2.4 bar	2.8 bar	3.2 bar	3.6 bar	4 bar	5 bar
5/10	6745/3060	8380/3800	10220/4635	11850/5375	13690/6210	15335/6955	16965/7695	18805/8530	20435/9270	
40/65	3750/1700	4650/2110	5675/2575	6580/2985	7605/3450	8520/3865	9425/4275	10450/4740	11355/5150	