

# FLOTXTRA



## SOIL PROTECTION

- Rounded tread lug edges ensure optimal protection of crop areas
- Wide tread lugs result in lower soil compaction
- Stiff tread design ensures even pressure distribution and a stable footprint.

## LATERAL STABILITY

- Special tread block design ensures excellent lateral grip
- Multi-oriented tread block faces ensure excellent self-cleaning properties.

## DURABILITY & MILEAGE

- Full-steel construction for excellent durability and damage resistance
- Advanced rubber compound construction ensures excellent mileage performance.

## SAFETY

- Limited stone and mud retention due to an advanced tread geometry design
- Excellent directional stability caused by the nearly continuous central rib.

SIZE	LOAD & SPEED	TYPE	RIM	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	STATIC LOADED RADIUS (mm)	ROLLING CIRC. (mm)	TREAD DEPTH (mm)
650/65R30.5 IMP	176 D	TL	AG20.00 x 30.5	645	1621	729	4910	23

### TYRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)

Service Speed (mph/kph)	12 psi	17 psi	23 psi	29 psi	35 psi	41 psi	46 psi	52 psi	58 psi	73 psi
	0.8 bar	1.2 bar	1.6 bar	2 bar	2.4 bar	2.8 bar	3.2 bar	3.6 bar	4 bar	5 bar
5/10	9290/4215	11550/5240	14090/6390	16335/7410	18885/8565	21130/9585	23380/10605	25925/11760	28175/12780	
40/65	5170/2345	6415/2910	7825/3550	9085/4120	10485/4755	11740/5325	12995/5895	14395/6530	15655/7100	