



SPECIFICATIONS

AGRIXTRA XL

FEATURES & BENEFITS:

The Maxam AGRIXTRA XL is a large volume R1W tyre designed specifically for use on high horsepower tractors. It boasts a 45-degree angle lug profile which ensures maximum traction and minimised vibration. The tyre's wide footprint profile ensures limited soil compaction.

An advanced radial tyre construction.

A self-cleaning tread design ensures exceptional traction and prolonged tyre life.

A wide tread footprint ensures excellent flotation, limited soil compaction and reduced crop damage.

Premium rubber compound construction ensures limited cracking and weathering for optimal durability and prolonged tyre life.



Size	2nd Size marking	LI/SS	Type	Recommended Rim (Inch)	Authorised Rim (Inch)	Tread Depth (mm)
600/70R30	-	158D/161A8	TL	DW20B	W18L, DW18L	51

Section Width on Rec Rim (mm)	Overall Diameter (mm)	Static Loaded Radius (mm)	Rolling Circumference (mm)	Speed Radius Index	# of Lugs	75% of Internal volume (l)
611	1602	709	4790	750	20 x 2	451

Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)										
	9 psi	12 psi	15 psi	18 psi	20 psi	23 psi	26 psi	29 psi	32 psi	35 psi	41 psi
	0.6 bar	0.8 bar	1 bar	1.2 bar	1.4 bar	1.6 bar	1.8 bar	2 bar	2.2 bar	2.4 bar	2.8 bar
5/10 LT	6315/2865	7155/3245	8005/3630	8840/4010	9690/4395	10530/4775	11045/5010	11565/5245	12085/5480	12600/5715	14055/6375
40/65			5955/2700	6570/2980	7200/3265	7830/3550	8215/3725	8600/3900	8985/4075	9370/4250	