

SPECIFICATIONS

AGRIXTRA H

FEATURES & BENEFITS:

The Maxam AGRIXTRA H is a large volume R1W tyre designed specifically for use on harvesting machines. It boasts a 45-degree angle lug profile which ensures maximum traction and minimised vibration. The tyre's wide footprint profile ensures limited soil compaction.

An advanced radial tyre construction.

A self-cleaning tread design ensures exceptional traction and prolonged tyre life.

A wide tread footprint ensures excellent flotation, limited soil compaction and reduced crop damage.

Premium rubber compound construction ensures limited cracking and weathering for optimal durability and prolonged tyre life.



Size	2nd Size marking	LI/SS	Type	Recommended Rim (Inch)	Authorised Rim (Inch)	Tread Depth (mm)
620/75R26	23.1R26	166A8/B	TL	DW20B	-	53

Section Width on Rec Rim (mm)	Overall Diameter (mm)	Static Loaded Radius (mm)	Rolling Circumference (mm)	Speed Radius Index	# of Lugs	75% of Internal volume (l)
611	1491	629	4458	700	18 x 2	472

Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)												
	15 psi	18 psi	20 psi	23 psi	26 psi	29 psi	32 psi	35 psi	38 psi	41 psi	44 psi	46 psi	55 psi
	1 bar	1.2 bar	1.4 bar	1.6 bar	1.8 bar	2 bar	2.2 bar	2.4 bar	2.6 bar	2.8 bar	3 bar	3.2 bar	3.8 bar
5/10 LT	8720/3955	9450/4285	10175/4615	10905/4945	11545/5235	12170/5520	12810/5810	13450/6100	14045/6370	14640/6640	15235/6910	15830/7180	17530/7950
40/65	6440/2920	6980/3165	7510/3405	8050/3650	8520/3865	8985/4075	9460/4290	9925/4500	10365/4700	10805/4900	11245/5100	11685/5300	