

SPECIFICATIONS

AGRIXTRA H

FEATURES & BENEFITS:

The Maxam AGRIXTRA H is a large volume R1W tyre designed specifically for use on harvesting machines. It boasts a 45-degree angle lug profile which ensures maximum traction and minimised vibration. The tyre's wide footprint profile ensures limited soil compaction.

An advanced radial tyre construction.

A self-cleaning tread design ensures exceptional traction and prolonged tyre life.

A wide tread footprint ensures excellent flotation, limited soil compaction and reduced crop damage.

Premium rubber compound construction ensures limited cracking and weathering for optimal durability and prolonged tyre life.



Size	2nd Size marking	LI/SS	Type	Recommended Rlm (Inch)	Authorised Rlm (Inch)	Tread Depth (mm)
650/75R32	24.5R32	172D/175A8	TL	DW21B	DW20B, DW23B	58

Section Width on Rec Rlm (mm)	Overall Diameter (mm)	Static Loaded Radius (mm)	Rolling Circumference (mm)	Speed Radius Index	# of Lugs	75% of Internal volume (l)
655	1789	787	5349	45 875	21 x 2	637

Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)												
	15 psi	18 psi	20 psi	23 psi	26 psi	29 psi	32 psi	35 psi	38 psi	41 psi	44 psi	46 psi	55 psi
	1 bar	1.2 bar	1.4 bar	1.6 bar	1.8 bar	2 bar	2.2 bar	2.4 bar	2.6 bar	2.8 bar	3 bar	3.2 bar	3.8 bar
5/10 LT	10145/4600	11210/5085	12280/5570	13350/6055	14045/6370	14750/6690	15455/7010	16165/7330	16790/7615	17420/7900	18060/8190	18685/8475	20835/9450
40/65	7540/3420	8335/3780	9130/4140	9925/4500	10450/4740	10970/4975	11500/5215	12015/5450	12490/5665	12955/5875	13430/6090	13890/6300	