



SPECIFICATIONS

AGRIXTRA XL

FEATURES & BENEFITS:

The Maxam AGRIXTRA XL is a large volume R1W tyre designed specifically for use on high horsepower tractors. It boasts a 45-degree angle lug profile which ensures maximum traction and minimised vibration. The tyre's wide footprint profile ensures limited soil compaction.

An advanced radial tyre construction.

A self-cleaning tread design ensures exceptional traction and prolonged tyre life.

A wide tread footprint ensures excellent flotation, limited soil compaction and reduced crop damage.

Premium rubber compound construction ensures limited cracking and weathering for optimal durability and prolonged tyre life.



Size	2nd Size marking	LI/SS	Type	Recommended Rim (Inch)	Authorised Rim (Inch)	Tread Depth (mm)
650/85R38	-	173D/176A8	TL	DW23B	DW20B, DW21B	62

Section Width on Rec Rim (mm)	Overall Diameter (mm)	Static Loaded Radius (mm)	Rolling Circumference (mm)	Speed Radius Index	# of Lugs	75% of Internal volume (l)
676	2071	914	6192	975	20 x 2	818

Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)										
	9 psi	12 psi	15 psi	18 psi	20 psi	23 psi	26 psi	29 psi	32 psi	35 psi	41 psi
	0.6 bar	0.8 bar	1 bar	1.2 bar	1.4 bar	1.6 bar	1.8 bar	2 bar	2.2 bar	2.4 bar	2.8 bar
5/10 LT	9700/4400	10990/4985	12280/5570	13570/6155	14875/6745	16165/7330	16945/7685	17715/8035	18500/8390	19285/8745	21500/9750
40/65			9130/4140	10100/4580	11060/5015	12015/5450	12600/5715	13175/5975	13760/6240	14335/6500	