



SPECIFICATIONS

AGRIXTRA XL

FEATURES & BENEFITS:

The Maxam AGRIXTRA XL is a large volume R1W tyre designed specifically for use on high horsepower tractors. It boasts a 45-degree angle lug profile which ensures maximum traction and minimised vibration. The tyre's wide footprint profile ensures limited soil compaction.

An advanced radial tyre construction.

A self-cleaning tread design ensures exceptional traction and prolonged tyre life.

A wide tread footprint ensures excellent flotation, limited soil compaction and reduced crop damage.

Premium rubber compound construction ensures limited cracking and weathering for optimal durability and prolonged tyre life.



Size	2nd Size marking	LI/SS	Type	Recommended Rim (Inch)	Authorised Rim (Inch)	Tread Depth (mm)
800/70R38	-	178D/181A8	TL	DW25B	-	62

Section Width on Rec Rim (mm)	Overall Diameter (mm)	Static Loaded Radius (mm)	Rolling Circumference (mm)	Speed Radius Index	# of Lugs	75% of Internal volume (l)
798	2061	921	6234	975	21 x 2	1072

Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)										
	9 psi	12 psi	15 psi	18 psi	20 psi	23 psi	26 psi	29 psi	32 psi	35 psi	41 psi
	0.6 bar	0.8 bar	1 bar	1.2 bar	1.4 bar	1.6 bar	1.8 bar	2 bar	2.2 bar	2.4 bar	2.8 bar
5/10 LT	11565/5245	13110/5945	14650/6645	16195/7345	17740/8045	19285/8745	20020/9080	20760/9415	21500/9750	22250/10090	24805/11250
40/65			10895/4940	12040/5460	13185/5980	14335/6500	14885/6750	15435/7000	15985/7250	16540/7500	